



Republic of the Philippines
CAVITE STATE UNIVERSITY
 Don Severino delas Alas Campus
 Indang, Cavite

BILL OF QUANTITIES

IMPROVEMENT OF AQUACULTURE, BIOLOGY, ENVIRONMENT, SCIENCE AND TECHNOLOGY (AQUABEST) BUILDING					
ABC: ₱ 2,149,111.56				Bill of Quantities	
COLLEGE/UNIT/CAMPUS: NAIC CAMPUS					
Item No.	Description	Unit	Quantity	Unit Price (Pesos)	Amount (Pesos)
I	MISCELLANEOUS WORKS (Pesos _____ _____ and _____ centavos)				
II	PAINTING WORKS (Pesos _____ _____ and _____ centavos)				
GRAND TOTAL					_____
Write grand total in words			_____ _____ _____		

Submitted by: _____ Date: _____
 Name of Bidder/Bidder's Representative: _____
 Position: _____
 Construction Company/Contractor: _____

CAVITE STATE UNIVERSITY

SCOPE OF WORK:

A. IMPROVEMENT OF AQUACULTURE, BIOLOGY, ENVIRONMENT, SCIENCE AND TECHNOLOGY (AQUABEST) BUILDING

GENERAL NOTES:

1. The project should be finished for 75 calendar days.
2. Actual site inspection is a must.
3. The area should be cleared/cleaned before and after the painting and miscellaneous work.
4. Mobilization
 - a. Provide the following:
 1. Billboard
 2. Bank house, temporary office and temporary comfort rooms
 3. Site enclosure

B. Technical Description

I. Miscellaneous Works (2 units fire escape)

A. Stainless Railing (fire escape with ladder)

1. Provide 1.5 mm thick stainless tubing for railings. Use 2" and 1" tubing.
2. Provide ¼" x 2" stainless flat bar with 2.0 mm. thick stainless tubing for ladder.
3. Provide stainless grills cover (0.60 m. x 0.60 m.)

B. Repair of existing gutter.

II. Painting Works

Painting of the whole building including canopy (top and bottom)

A. Wood

1. Apply one coat of flatwall enamel white. Allow to dry overnight.
2. Repair minor surface imperfection with glazing putty. Let dry then sand.
3. Apply at least two (2) coats of Quick Dry Enamel in the desired color. Allow an overnight intercoating interval.

B. Metal

1. Apply epoxy primer by brush or spray. Allow to dry for 24 hours. Apply suitable putty on imperfections, then sand.
2. Apply at least two (2) coats of Quick dry Enamel in the desired color.

C. Concrete

1. Treat the surface with concrete neutralizer. Mix one part with 16 parts water by volume.
2. Apply latex flat as primer. Repair minor surface imperfections with a suitable putty. Let dry, then sand.
3. Apply at least two (2) coats of colored dirt resistant semi gloss latex paint (factory mixed)

Note: Color of paint will depend upon the preference of the end-user. Paints and its accessories should be BOYSEN of approved equal.

- C. Consult the end-user and project inspector for details and extent of work. The silence of specifications, plans, special provisions and supplementary specifications as to any detail, or the apparent omission therein of detailed description or definition of the quality of materials and workmanship shall be regarded to mean that only materials and workmanship of first class quality are to be used or employed.