

Supply, Delivery and Installation of LED Wall for Rolle Hall


ABC: 1,650,500.00


	P3.9 RW3 series Indoor led display with nano coating 3.9mm physical pixel pitch, module size 250mmx250mm: screen size 2.5mmx5mm: 64x64 dot resolution module cabinet size: 500mmx500mmx79mm, 600W/m2 power consumption, 3000 - 10000K color temp., IP30 grade with 16 bits gray scale, contract ratio 3000:1, die cast aluminum cabinet.(50 cabinets)	50
1 Lot	HD Video processor, 4 input HD digital video switcher with video effect, built-in animation and backgrounds built-in audio mixer, Professional 10-bit processing switcher, Video standard: HD, 2x HD-SDI / 2x HDMI Video input, HDMI Output(1 is MV is assignable) 1x HD-SDI. FTB, Cut 32 wife with border Effects and 22" (21.5" Viewable) LED monitor	1
	Laptop i7 processor, 8GB DDR4 memory, 256 SSD storage + 1TB HDD, 15.6 LED display, 4GB GDDR5 RAM with type C USB/ RJ45/HDMI/USB 3.1 and 3.5mm audio jack HDMI cable connectors and UTP Line input cables Fixed installation with steel back frame fully painted Powerline with breaker protection and surge protector 20KV or compatible Auto Voltage Regulator	1

Prepared by:


GUILLERMO P. DESENGANIO
OBA Director

Certified Correct:


EMELINE C. GUEVARRA
TWG Chair, Computer and Office Equipment


DINDO C. MARGES
TWG Member, Computer and Office Equipment