



Republic of the Philippines
CAVITE STATE UNIVERSITY
 Don Severino delas Alas Campus
 Indang, Cavite

BILL OF QUANTITIES

REPAINTING OF BUILDING AT CARMONA CAMPUS			Bill of Quantities		
ABC: ₱ 1,231,645.87					
COLLEGE/UNIT/CAMPUS: CARMONA CAMPUS					
Item No.	Description	Unit	Quantity	Unit Price (Pesos)	Amount (Pesos)
I	SCRAPING AND CLEANING WORKS (Pesos _____ _____ and _____ centavos)				
II	SCAFFOLDING AND MISCELLANEOUS WORKS (Pesos _____ _____ and _____ centavos)				
III	PAINTING WORKS (Pesos _____ _____ and _____ centavos)				
GRAND TOTAL					_____
Write grand total in words		_____ _____ _____			

Submitted by: _____ Date: _____
 Name of Bidder/Bidder's Representative: _____
 Position: _____
 Construction Company/Contractor: _____

CAVITE STATE UNIVERSITY

SCOPE OF WORK:

A. REPAINTING OF BUILDING AT CARMONA CAMPUS

GENERAL NOTES:

1. The project should be finished for 35 calendar days.
2. Actual site inspection is a must.

B. Technical Description

I. Scraping and Cleaning Works

1. Remove all chalky surface, loose paint, dirt and other contaminants by wire brushing or by using paint remover.
2. The area should be cleared/cleaned before and after the construction work at least six meters away from the building line. Unusable used formworks, excessive soil fill and all other unwanted debris of construction works should be disposed properly.

II. Scaffolding and Miscellaneous Works

1. Provide necessary form lumber and scaffolding needed for the completion of the project.

III. Painting Works

The whole building should be painted (both exterior and interior).

1. Wood
 - a. Apply one coat of flatwall enamel white. Allow to dry overnight.
 - b. Repair minor surface imperfections with glazing putty. Let dry for 3-4 hours then sand.
 - c. Apply two coats of semi gloss enamel in the desired color. Allow an overnight intercoating interval.
2. Metal
 - a. Apply epoxy primer by brush or spray. Allow to dry for 24 hours. Apply suitable putty on imperfections, then sand.
 - b. Apply at least two coats of Quick Dry Enamel in the desired color.
3. Concrete
 - a. Repair minor surface imperfections with a suitable putty. Let dry, then sand. Spot coat with top coat color.
 - b. Apply two coats of colored elastomeric paint or factory mixed dirt resistant semi-gloss latex. Apply with brush or roller.
 - c. Cleaning of ashline. Application of acrylic emulsion. Top coat with an acrylic solvent based clear coating.

Note: Color of paint will depend upon the preference of the end user. Paints and its accessories should be BOYSEN or approved equal.