



Republic of the Philippines
CAVITE STATE UNIVERSITY
 Don Severino delas Alas Campus
 Indang, Cavite

BILL OF QUANTITIES

PAINTING AND MISCELLANEOUS WORKS FOR THE GRADUATE SCHOOL AND OPEN LEARNING COLLEGE BUILDING ABC: ₱ 1,147,117.69 COLLEGE/UNIT/CAMPUS: MAIN CAMPUS					
				Bill of Quantities	
Item No.	Description	Unit	Quantity	Unit Price (Pesos)	Amount (Pesos)
I	MISCELLANEOUS WORKS (Pesos _____ _____ and _____ centavos)				
II	PAINTING WORKS (Pesos _____ _____ and _____ centavos)				
GRAND TOTAL					_____
Write grand total in words					_____ _____ _____

Submitted by: _____ Date: _____
 Name of Bidder/Bidder's Representative: _____
 Position: _____
 Construction Company/Contractor: _____

CAVITE STATE UNIVERSITY

SCOPE OF WORK:

A. PAINTING AND MISCELLANEOUS WORKS FOR THE GRADUATE SCHOOL AND OPEN LEARNING COLLEGE BUILDING

GENERAL NOTES:

1. The project should be finished for 60 calendar days.
2. Site inspection is a must. There is an existing newly built structure.
3. The area should be cleared before and after the construction works at least six meters away from the building line. Unusable used formworks and all other unwanted debris of construction works should be disposed properly.

B. Technical Description

I. Miscellaneous Works

A. Supply and Installation of the following:

1. Heavy duty PVC Accordion Partition Wall at second and third floors (grid B, C, & D/2 to 4)
2. Aluminum glass door, complete with heavy duty accessories. (2 - sets)
3. Water proofing:
 - application of flexible cement tissue with concrete topping for the whole concrete gutter.

II. Painting Works (PAINTING OF THE WHOLE BUILDING)

A. Wood / Metal

1. Apply one coat of wood/steel primer paint. Allow to dry overnight.
2. Repair minor surface imperfection with glazing putty. Let dry then sand.
3. Apply at least two coats of Quick Dry Enamel in the desired color. Allow an overnight inter coating interval.

B. Steel Reinforcement

1. Treat the surface with concrete neutralizer. Mix one part with 16 parts water by volume.
2. Apply skim coat for plain finishing/improving surface imperfections of concrete surfaces. Let dry, then sand.
3. Apply Latex flat as primer.
4. Apply at least two coats of colored (factory mixed) dirt resisting semi gloss latex paint.

Note: Color of paint will depend upon the preference of the end-user. Paints and its accessories should be BOYSEN or approved equal.

- C. See plans/consult the end-user and project inspector for details and extent of work.