



Republic of the Philippines  
**CAVITE STATE UNIVERSITY**  
**Don Severino de las Alas Campus**

Indang, Cavite, Philippines

☎ (046) 4150-010 / 📠 (046) 4150-0013 loc 203

[www.cvsu.edu.ph](http://www.cvsu.edu.ph)

**INVITATION TO SUBMIT QUOTATION**

**Labor for Replacement of Ceiling of Veterinary Molecular Diagnostic Laboratory (By Administration – Pakyaw Labor Group)**


1. The Cavite State University (CvSU) invites interested firms/supplier to submit quotation for the project “**Labor for Replacement of Ceiling of Veterinary Molecular Diagnostic Laboratory (By Administration – Pakyaw Labor Group)**” with an Approved Budget for the Contract (ABC) of **Seventy-Three Thousand Sixty-Five Pesos and 93/100 Only (PhP 73,065.93)**. Quotation received in excess of the ABC shall be automatically rejected at the opening.

Item No.	Quantity	Unit	Description	Unit Cost	Total Cost
1.	1	Lot	Labor for Replacement of Ceiling of Veterinary Molecular Diagnostic Laboratory (By Administration – Pakyaw Labor Group)  Scope of Work: <ul style="list-style-type: none"> <li>● Site Clearing and Preparation</li> <li>● Carpentry Works</li> <li>● Electrical Works</li> <li>● Painting Works</li> </ul>		73,065.93
<b>TOTAL AMOUNT</b>					<b>73,065.93</b>

2. Delivery Period: \_\_\_\_ calendar days from the receipt of P.O.
3. Price quotations must be valid for a period of sixty (60) calendar days from date of submission and shall include all taxes, duties and/or levies payable. Bidders shall also indicate the brand and model of the items being offered.
4. Warranty shall be for a period of six (6) months for supplies and materials. Warranty for equipment must not be less than one (1) year from the date of acceptance and shall be accompanied with Warranty Certificate.
5. The quotation must be submitted to the Supply Office through mail, fax or email at the contact details listed below **on or before 5:00 PM of October 20, 2022**.

Address : Supply Office, Administration Building  
Cavite State University  
Indang, Cavite  
E-mail : [supplyoffice@cvsu.edu.ph](mailto:supplyoffice@cvsu.edu.ph)  
Telefax : (046) 862-0852

6. The CvSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. CvSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.



**ROSELYN M. MARANAN**

BAC Secretary, Goods and Services



## BILL OF QUANTITIES

NAME OF PROJECT: LABOR FOR REPLACEMENT OF CEILING OF VETERINARY MOLECULAR DIAGNOSTIC LABORATORY (BY ADMINISTRATION – PAKYAW LABOR GROUP) ABC: ₱ 73,065.93 COLLEGE/UNIT/CAMPUS: CVMBS, CVSU- INDANG CAMPUS					
Bill of Quantities					
Item No.	Description	Unit	Quantity	Unit Price (Pesos)	Amount (Pesos)
I	<b>SITE CLEARING AND PREPARATION</b> (Pesos _____ _____ and _____ centavos)				
II	<b>CARPENTRY WORKS</b> (Pesos _____ _____ and _____ centavos)				
III	<b>ELECTRICAL WORKS</b> (Pesos _____ _____ and _____ centavos)				
IV	<b>PAINTING WORKS</b> (Pesos _____ _____ and _____ centavos)				
<b>GRAND TOTAL</b>		_____			
<b>Write grand total in words</b>		_____ _____ _____			

Submitted by: \_\_\_\_\_ Date: \_\_\_\_\_

Name of Bidder/Bidder's Representative: \_\_\_\_\_

Position: \_\_\_\_\_

Construction Company/Contractor: \_\_\_\_\_

## **A. REPLACEMENT OF CEILING OF VETERINARY MOLECULAR DIAGNOSTIC LABORATORY AT CVMBS**

1. The project must be finished in 30 working days
2. Actual site inspection is a must.
3. The area should be cleared before and after the construction work at least twelve meters away from the job site. Unusable formworks, excessive soil fill and all other unwanted debris of rehabilitation works should be disposed properly.

## **B. TECHNICAL DESCRIPTION**

### **I. Site Clearing**

1. Dismantling of existing ceiling including ceiling joist and lighting fixtures.
2. This work will include restoration of furniture and hauling of debris.
  - a. All debris must be disposed properly.

### **II. Carpentry Works**

1. Installation of Ceiling
  - a. Use 25mm x 25mm x .60mm thk. Wall angle
  - b. Use 1" concrete nail for fastening wall angle at concrete
  - c. Use .60mm x 19mm x 50mm x .60mm thk. J-furring as ceiling joist, parallel to the longer sides of the room spaced at 40mm middle on center
  - d. Use 1mm x 12mm x 38mm x 1.0mm thk. C-channel as ceiling joist, parallel to the shorter sides of the room spaced at 400mm middle on center
  - e. Use .55mm x 12mm x 38mm x .55mm thk. C-channel for ceiling hanger every 800mm middle on center
  - f. Use 3/16" thk. x 1.20m x 2.40m fibercement board for ceiling boards
  - g. Installation of 1" x 2" KD cornice

### **III. Electrical Works**

1. Roughing-in
  - a. This work will include re-installation of the following:
    - a.1. Lighting outlet electrical layout
2. Installation of lighting fixtures.
3. Tap to existing source.

### **IV. Painting Works**

1. Ceiling
  - a. Surface Preparation
    - a.1. Affix drywall boards following specific standard installation guidelines by the board manufacturer.
    - a.2. Sand rough surfaces until smooth, then dirt off before painting.
    - a.3. Surface to be painted should be clean and dry, free from dust, dirt and other foreign matter
  - b. Painting application
    - b.1. Prime bare substrate with flat latex. Let dry for 6 to 8 hours.
    - b.2. Putty minor surface imperfections with suitable putty. Let dry for 6 to 8 hours. Spot prime puttied portions.
    - b.3. Finish with at least two (2) coats of semi gloss latex. Let dry for 6 to 8 hours in between coats.
2. Cornice
  - a. Surface Preparation
    - a.1. Use only kiln dried wood.
    - a.2. Countersink nail heads for putty application.
    - a.3. Sand rough wood until smooth, then dust off before painting.
    - a.4. Surface to be painted should be clean and dry, free from dust, dirt and other foreign matter.

- b. Painting application
  - b.1. Prime bare substrate with flatwall. Let dry for 6 to 8 hours.
  - b.2. Putty minor surface imperfections with suitable putty. Let dry for 6 to 8 hours. Spot prime puttied portions.
  - b.3. Finish with at least two (2) coats quick drying enamel, chocolate brown. Let dry for 6 to 8 hours in between coats.

**V. Note**

1. See/consult end user for details/extent of work. The silence of specification, plans, special provision and supplementary specifications as to any detail, or the apparent omission therein of a detailed description or definition of the quality of materials and workmanship shall be regarded to mean that only materials and workmanship of first class quality are to be used or employed.
2. All works will be facilitated by the contractor.
3. All tools and equipment necessary for executing the work will be provided by the end-user/PPS office.
4. Works that are necessary but are not cited in the above specifications will be facilitated by the PPS office.
5. Materials that are necessary but are not included in the above program of works will be provided by the end user.
6. No modifications will be done without the approval of end user, project inspector and implementor.
7. Verify actual measurement on site.