## Republic of the Philippines CAVITE STATE UNIVERSITY

### Don Severino de las Alas Campus

Indang, Cavite, Philippines

(046) 4150-010 / (046) 4150-0013 (oc 203)

www.cvsu.edu.ph

# INVITATION TO SUBMIT QUOTATION Labor for Repair and Repainting of Perimeter Fence Along Bancod Road (By Administration)

 The Cavite State University (CvSU) invites interested firms/supplier to submit quotation for the project "Labor for Repair and Repainting of Perimeter Fence Along Bancod Road (By Administration)" with an Approved Budget for the Contract (ABC) of Two Hundred Thirty-Five Thousand One Hundred Twenty-Three Pesos and 83/100 Only (PhP 235,123.83). Quotation received in excess of the ABC shall be automatically rejected at the opening.

Item No.	Quantity	Unit	Description	Unit Cost	Total Cost
1.	1	Lot	Labor for Repair and Repainting of Perimeter Fence Along Bancod Road (By Administration)  Scope of Works: - Earthworks - Masonry Works - Painting Works	235,123.83	235,123.83
TOTAL AMOUNT					

- 2. Delivery Period: calendar days from the receipt of P.O.
- 3. Price quotations must be valid for a period of sixty (60) calendar days from date of submission and shall include all taxes, duties and/or levies payable. Bidders shall also indicate the brand and model of the items being offered.
- 4. Warranty shall be for a period of six (6) months for supplies and materials. Warranty for equipment must not be less than one (1) year from the date of acceptance and shall be accompanied with Warranty Certificate.
- 5. The quotation must be submitted to the Supply Office through mail, fax or email at the contact details listed below **on or before 5:00 PM** of **November 21, 2022.**

Address : Supply Office, Administration Building

Cavite State University

Indang, Cavite

E-mail : <u>supplyoffice@cvsu.edu.ph</u>

Telefax : (046) 862-0852

6. The CvSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. CvSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

ROSELYN M. MARANAN
BAC Secretary, Goods and Services



#### Republic of the Philippines

#### CAVITE STATE UNIVERSITY

Don Severino delas Alas Campus

Indang, Cavite

#### **BILL OF QUANTITIES**

PERIM	OF PROJECT: REPAIR AND REPAIN METER FENCE ALONG BANCOD ROA NISTRATION)				
ABC:	P 403,661.50 EGE/UNIT/CAMPUS: CvSU INDANG C	Bill of Quantities			
Item No.	Description	Unit	Quantity	Unit Price (Pesos)	Amount (Pesos)
1	Earth Works (Pesos and centavos)				
11	Masonry Works (Pesos andcentavos)				
III	Painting Works (Pesos andcentavos)				
	GRAND TOTAL				
	Write grand total in words				
ubmitte	ed by:		Da	te:	
osition:					
nstruc	ction Company/Contractor:				

#### SCOPE OF WORKS:

#### A. REPAIR AND REPAINTING OF PERIMETER FENCE ALONG BANCOD ROAD

1. The project should be finished for 75 calendar days.

#### **B. TECHNICAL DESCRIPTION**

#### I. Earthworks

- This work includes the excavation and removal of tree roots causing obstruction.
- Uprooted roots should be disposed properly.

#### II. Masonryworks

- This work includes the plastering of existing masonry of perimeter fence and the repair of
  - damaged panels of perimeter fence.
- Clean the area of unnecessary stains or dirt.
- Masonry should be plastered with plain cement finish.
- Consult the project inspectors for the details and extent of work.

#### III. Painting Works

- This work includes the repainting of steel grills and masonry components of the perimeter fence.
- Consult the project inspectors for the details and extent of work.

#### FOR METAL/STEEL

- Apply rust converter/rust remover and epoxy primer by brush or spray.
   Allow to dry for 24 hours. Apply a suitable putty on imperfections. Sand to a smooth finish.
- Apply two coats of Quick Dry Enamel in the desired color.

#### FOR CONCRETE/MASONRY

- Repair minor surface imperfections with skimcoat. Let dry, sand then, spot coat with top coat color.
- 2. Apply two coats of colored factory mixed dirt resisting semi-gloss latex.

NOTE: Color of paint will depend upon the preference of the end-user.

Paints and its accessories should be boysen or approved equal.