



Republic of the Philippines  
**CAVITE STATE UNIVERSITY**  
**Don Severino de las Alas Campus**  
 Indang, Cavite, Philippines  
 ☎ (046) 889-6373  
[www.cvsu.edu.ph](http://www.cvsu.edu.ph)

**INVITATION TO SUBMIT QUOTATION**  
**Supply and Delivery of ICT Equipment, Accessories and Peripherals for GADRC**

1. The Cavite State University (CvSU) invites interested firms/supplier to submit quotation for the project **“Supply and Delivery of ICT Equipment, Accessories and Peripherals for GADRC”** with an Approved Budget for the Contract (ABC) **Two Hundred Sixteen Thousand Three Hundred Two Pesos and 90/100 Only (PhP 216,302.90)**. Quotation received in excess of the ABC shall be automatically rejected at the opening.

Item No.	Quantity	Unit	Description	Unit Cost	Total Cost
1.	5	Units	Headset, Noise Cancelling Microphone, and Volume Adjuster for Webinar / Computer Internet Calls / Communication (Black)	1,000.00	5,000.00
2.	3	Units	Keyboard, USB-type	490.00	1,470.00
3.	3	Units	Monitor, 24" LED	14,500.00	43,500.00
4.	3	Units	PRINTER, MULTIFUNCTION, print, copy, scan, fax, wifi, with top feeder	15,000.00	45,000.00
5.	1	Unit	Projector with VGA and HDMI port • Imaging device, number: DMDx1 • DMD: Number of pixels: 1024x768 (XGA); Size: 0.55 type/4:3 • Projection Lens: Zoom ratio/Focal length: 1x1/22.0-4.1mm Zoom ratio/Focal length: 1x1/22.0-4.1mm F2.56-2.68; Projection distance: W: 2.38-7.15 m; T: 2.62-7.87 m • Projection distance for 100": 3.97-4.37 m Projection ratio (*1): 1.96:1-2.15:1 • Operation: Zoom: manual, Focus: manual • Light Source: Lamp type - Super-high pressure lamp for projectors; Lamp power-210/170 W • Image Signal: Analog PC input: UXGA/SXGA+ WXGA+/FWXGA/WXGA/SXGA/XGA/SVGA/ VGA/MAC; Digital PC Input: UXGA / SXGA+ / WXGA+ / FWXGA / WXGA/ SXGA / XGA / SVGA / VGA • Digital Video Input: 1080p / 1080i / 720p / 576p / 480p • MHL Input:1080p/1080i/720p /576p / 576i/480p/480i • Component Video Input: 1080p / 1080i / 720p / 576p / 576i / 480p /480i	40,000.00	40,000.00

			<ul style="list-style-type: none"> <li>• Video input/S-video input: NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N / PAL-60</li> <li>Terminal: Mini D-sub 15pin x 2: Analog PC/</li> <li>Component video input</li> <li>• HDMI (MHL): Digital PC/Digital video/MHL Input</li> <li>• RCA: Composite video input; Mini DIN4: S-video input; Mini jack: Audio input; Dsub9:</li> <li>RS-232C connection; RJ45: 100BASE-TX/10BASE-T</li> <li>• USB type B: Service port</li> </ul> <p>Mechanics:</p> <p>Adjustable feet: Front: 1 Rear: 1 (the angle elevation of up to 6°)</p> <p>Speaker: 10 W, monaural; Dimensions (WxH xD): W: 282 mm, H:114.5 mm, D:232 mm</p> <p>Weight: 2.5 kg (5.5 lbs); Noise: 38/31dB</p> <p>Others:</p> <ul style="list-style-type: none"> <li>• Power supply: AC100V-240V 50/60Hz</li> <li>• Power consumption: 350 W/240 W</li> <li>• Standby power consumption: 3.0W (standby)</li> <li>• Accessories: Remote control LV-RC08, Computer Cable, Power Cord</li> </ul>		
6.	5	Units	<p>Web camera: HD 1080P</p> <ul style="list-style-type: none"> <li>• 1080p for sharp and clear images</li> <li>• Built-in Omni directional microphone</li> <li>• Wide angle lens</li> <li>• Flexible rotation</li> <li>• USB plug and play</li> <li>• No drivers required</li> </ul>	1,500.00	7,500.00
7.	2	Units	<p>Lapel Microphone</p> <p>System Specification:</p> <ul style="list-style-type: none"> <li>• Modulation Mode: Digital Frequency Modulate</li> <li>• Oscillation: PPL Synthesized; Carrier Frequency</li> <li>• Range: UHF 500-980 MHz;</li> <li>• Preset Frequencies: 48 (auto paring)</li> <li>• Frequency Response: 75 Hz-18kHz+ 3dB</li> <li>• Max Deviation Range: ±50kHz (with level limiting)</li> <li>• T.H.D.: &lt;1.0% @1kHz; S/N" &gt;98dB</li> <li>• Working Range: Up to 50m</li> <li>• RF Carrier Stability: ±0.005% (-10°C- 50°C)</li> <li>• Mini Wireless Receiver (Metal):</li> </ul> <p>Dimension: 93x31x20mm</p>	3,000.00	6,000.00

			<ul style="list-style-type: none"> <li>● Power supply: Built-in Li-on rechargeable battery (500mA); Power consumption: 80mA</li> <li>● Battery Life: Up to 6 hrs; Recharging Time: About 1 hour (5V/1A)</li> </ul> <p>Package contents:</p> <ul style="list-style-type: none"> <li>● 1 x Bodypack Transmitter</li> <li>● 1 x Portable Mini Receiver</li> <li>● 1 x Headset Microphone</li> <li>● 1 x Lavalier Microphone</li> <li>● 1 x USB charging cable</li> <li>● 1 x 3.5mm to 6.35 mm adapter</li> <li>● 1 x Headphone splitter</li> <li>● 1 x user manual</li> </ul>		
8.	5	Units	<p>UPS</p> <ul style="list-style-type: none"> <li>● Output Voltage Range: 200-255 +/- 5vac</li> <li>● Output Frequency: 50Hz / 60Hz ± 0.5Hz (Batt. Mode)</li> <li>● Wave Form: PWM (DC Mode)</li> <li>● Transfer Time: 2~6ms</li> <li>● Capacity &amp; Quantity of Battery: 12V (1*12V/9AH)</li> <li>● Charging Period: 4-6 Hours</li> <li>● Backup Time: 3-15minutes</li> <li>● Transformer Size &amp; Material: 96*45mm Aluminum</li> <li>● Wattage: 525W</li> <li>● Product Dimension(mm): 324*100*153"</li> </ul>	3,500.00	17,500.00
9.	1	Unit	<p>Document/ Image Scanner</p> <p>Supported operating systems Windows 10 (32-bit/64-bit), Windows 8/8.1(32-bit/64-bit), Windows 7 (32-bit / 64-bit), Windows Vista (32-bit / 64-bit), Windows Server 2012 R2 (64-bit), Windows Server 2012 (32-bit /64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008 (32-bit / 64-bit), LinuxUbuntu</p> <ul style="list-style-type: none"> <li>● Scanner type: ADF (Automatic Document Feeder)</li> <li>● Scanning Modes: Simplex/Duplex, Color/Grayscale/Monochrome</li> <li>● Image Sensor Type: Single line CMOS-CIS x 2 (Front x 1, Back x 1)</li> <li>Light Source: R,G,B LED x 2 (Front x 1, Back x 1)</li> <li>● Document Size: Maximum: A4 Portrait (210x297 mm) or Legal (8.5x 14 in.) or 8.5 x 34 in. (215.9 x 863.6 mm) (longpage scanning: 3,048 mm)</li> </ul>	49,999.00	49,999.00

			<p>(120 in.)) Minimum: A8 Portrait / Landscape (52 x 74 mm)</p> <p>Scanning speed (A4, Portrait) for Color, Grayscale, Monochrome:</p> <p>Simplex - 30 ppm (200 dpi/300 dpi);</p> <p>Duplex - 60 ipm (200 dpi/300 dpi)</p> <ul style="list-style-type: none"> <li>● Paper chute capacity (A4 Landscape): 50 sheets (A4: 80 g/m2 or 20 lb)</li> </ul> <p>Expected daily volume: 4,500 sheets/day</p> <p>Background colors: White (Hardware, scanned background is gray)</p> <ul style="list-style-type: none"> <li>● Optical Resolution: 600 dpi</li> <li>● Output Resolution: Color (24-bit), Grayscale (8-bit), Monochrome (1-bit): 50 dpi to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver)</li> <li>● Output Format: Color: 24-bit; Grayscale: 8-bit; Monochrome: 1-bit</li> </ul> <p>Internal Video processing: 65,536 levels (16-bit)</p> <p>Interface: USB2.0; Connector shape: B type;</p> <p>Image processing function: Auto color detection,</p> <p>Automatic page size detection, De-Skew, Multi-image, Blank page skip, Error diffusion, Dropout color (R, G, B, Saturation), Image emphasis, Advanced DTC, sRGB, Halftone, Smoothing, Split image, Vertical streaks reduction, Digital endorser, Edge correction, Dynamic threshold (iDTC)</p> <ul style="list-style-type: none"> <li>● Power requirement: AC 100 V to 240 V <math>\pm</math> 10%; Power Consumption: Operating - 18 W or less; Sleep mode - 1.6 W or less; Auto standby (OFF) mode - 0.4 W or less</li> <li>● Dimensions: Width x Depth x Height 298 mm x 135 mm x 133 mm (11.7 in. x 5.3 in. x 5.2 in.) Weight: 2.5 kg</li> </ul> <p>Included software / drivers: PaperStream IP for SP Series driver (TWAIN/TWAIN x64/ISIS), WIA Driver, PaperStream Capture Lite, Software Operation Panel, Error Recovery Guide, Presto! PageManager, ABBYY FineReader Sprint Scanner Central Admin</p> <p>Multifeed detection" Yes (Standard)</p> <p>ultrasonic multifeed detection sensor x 1;</p> <p>Long page scanning: 3,048 mm (120 in.)</p> <p>Included items: AC adapter, USB Cable, Setup DVD-ROM</p>		
10.	3	Units	MOUSE, OPTICAL, USB connection type	111.30	333.90
<b>TOTAL AMOUNT</b>					<b>216,302.90</b>

2. Delivery Period: \_\_\_\_ calendar days from the receipt of P.O.
3. Price quotations must be valid for a period of sixty (60) calendar days from date of submission and shall include all taxes, duties and/or levies payable. Bidders shall also indicate the brand and model of the items being offered.
4. Warranty shall be for a period of six (6) months for supplies and materials. Warranty for equipment must not be less than one (1) year from the date of acceptance and shall be accompanied with Warranty Certificate.
5. The quotation must be submitted to the Procurement Office through mail, fax or email at the contact details listed below **on or before 5:00 PM of February 26, 2024.**

Address : Procurement Office, Administration Building  
Cavite State University  
Indang, Cavite  
E-mail : [procurementoffice@cvsu.edu.ph](mailto:procurementoffice@cvsu.edu.ph) / [rfqmain@cvsu.edu.ph](mailto:rfqmain@cvsu.edu.ph)  
Telefax : (046) 889-6373

6. The CvSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. CvSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

  
**ROSELYN M. MARANAN**  
BAC Secretary, Goods and Consulting Services