

Republic of the Philippines **CAVITE STATE UNIVERSITY Don Severino de las Alas Campus** Indang, Cavite, Philippines (046) 889-6373 www.cvsu.edu.ph

## INVITATION TO SUBMIT QUOTATION

Supply and Delivery of Office Equipment, Peripherals and Accessories for CON

 The Cavite State University (CvSU) invites interested firms/supplier to submit quotation for the project "Supply and Delivery of Office Equipment, Peripherals and Accessories for CON" with an Approved Budget for the Contract (ABC) of Nine Hundred Sixty-Two Thousand Five Hundred Pesos Only (PhP 962,500.00). Quotation received in excess of the ABC shall be automatically rejected at the opening.

ltem No.	Quantity	Unit	Description	Unit Cost	Total Cost
1.	10	Units	<ul> <li>Printer, All-in-One, CISS</li> <li>Wireless / Ethernet, Print, Copy, Scan, Cloud Link with Continuous Ink Supply System (CISS), Up to 9600 [1] x 2400 dpi</li> <li>Compact integrated tank design, Weight: approx. 7.9 kg, Dimensions (W x D x H): approx. 435 x 370 x 148 mm</li> <li>High yield ink bottles in black, magenta, cyan, yellow, Power Source: AC 100-240V, 50/60Hz</li> <li>Spill-free, error-free refilling</li> <li>Borderless printing up to 4R</li> <li>IPrint Resolution: Up to 9600 [1] x 2400 dpi</li> <li>Scanner Type: CIS flatbed photo and document scanner</li> <li>Scanner Resolution (Optical): 2400 x 4800 dpi [6], Supported Operating Systems: Windows 10</li> </ul>	10,500.00	105,000.00
2.	17	Units	Surge Protector/Voltage Regulator/UPS Output Power Capacity: 325 Watts/650VA Output Frequency: 50/60 Hz +/-1 Hz Output Connections: (2) Universal Receptacle Nominal Input Voltage: 230V, Input Connections: NEMA 5-15P Maximum Input Current: 5A, Battery Type: Maintenance-free sealed Lead-Acid battery with suspended electrolyte leakproof Recharging Time: 4 Hours Output Frequency (sync to mains) 50/60 Hz +/-1 Hz Transfer Time 4ms typical : 6ms maximum	3,200.00	54,400.00

3.	3	Units	Mic and Speaker System, All-in-one, Wireless • Built-In Wheels and Handles, 2 x Wireless Microphones • Play Audio via Bluetooth, USB & SD Card • 10"" Woofer, 1"" Tweeter, 1/4"" and XLR Microphone Input Jacks • 60W RMS Class-D Amplifier, Onboard Mixer with Tone & Reverb Control • 3.5mm Aux Input and RCA Line Inputs • USB-C cable • Safety sheet, warranty card	18,742.57	56,227.72
4.	13	Units	Television, Smart TV, 55 inches • Dimension of TV without stand (W X H X D): 971 x 575 x 77 mm • Dimension of TV with stand (STANDARD POSITION) (W X H X D): 971 x 619 x 231 mm • Dimension of package carton (W X H X D): Approx. 1,051 x 671 x 143 mm • Wi-Fi Certified 802.11a/b/g/n/ac • Version 5.0, HID (mouse/keyboard connectivity)/HOGP (Low Energy device connectivity)/Advanced Audio Distribution Profile (stereo audio) 2/AVRCP (AV remote control) /SPP (Serial Port Profile)	49,999.00	649,987.00
5.	15	Units	<ul> <li>Wall bracket, TV</li> <li>26-55 Inches LED LCD PDP Flat Panel Tv</li> <li>Wall Mount Bracket Suitable For 26-55, Fits Most 26-55' Flat Panel TV</li> <li>With Vesa Compiance: 200*200mm</li> <li>With Load Capacity: 100ibs (45kg)</li> <li>Can be tilted Angle Up And Down 15</li> </ul>	3,000.00	45,000.00
6.	13	Units	<ul> <li>Wire cable, HDMI</li> <li>Cable length: 5 meters, High-speed</li> <li>HDMI to HDMI cable</li> <li>Works with HDTVs, digital cameras/camcorders, MP3 players, and other HDMI devices</li> <li>Supports Ethernet, 3D, and Audio Return</li> <li>Meets HDMI 1.4 specifications; shielded to defend against interference</li> <li>Durable braided design against wear and tear</li> </ul>	1,000.00	13,000.00
7.	16	Units	<ul> <li>Wire cable, VGA</li> <li>High performance VGA cable connects a VGA (Video Graphic Array) equipped computer to a monitor or projector with 15- pin VGA port (also known as RGB, DB-15, DE-15, HD-15, HDB-15 or D-sub 15) for video editing, gaming, or video projection</li> <li>Supports resolutions at 800x600 (SVGA), 1024x768 (XGA), 1600x1200</li> </ul>	704.33	11,269.28

9.       16       Initial constraints       Image: 1X VGA Cable         9.       16       Units       Package: 1X VGA Cable         8.       16       Wire extension       0.6-gang universal outlet with individual switch         8.       16       Units       Rigid brass strips for internal connection         0.Utlets are made of copper material for better grip       Inpact resistant and highly conductive       1,102.50         17,640.00       connection for safety       With REAL grounding system       1,102.50       17,640.00         0.Units       Units       Current: 10A, Voltage: 250V, Cord       17,640.00       10,640.00         9.       Units       Presentation Clicker, Wireless       Plug & Play: no software to install, easy to use       1,102.50       17,640.00         9.       16       Units       Presentation Clicker, Wireless       1,102.50       17,640.00         0.01et enclosures are made up of fire-retardant materials, Maximum wattage: 250V, Cord       2500W       10       10,08 Units       10,08 U			<ul> <li>and unplugging, and finger-tightened</li> <li>screws for a secure connection</li> <li>Foil and braid shielding on the VGA wire</li> </ul>		
9.       16       Units <ul> <li>Random color of black or white</li> <li>Wire extension</li> <li>6-gang universal outlet with individual switch</li> <li>Rigid brass strips for internal connection</li> <li>Outlets are made of copper material for better grip</li> <li>Impact resistant and highly conductive</li> <li>With REAL grounding system</li> <li>1,102.50</li> <li>17,640.00</li> <li>With NEAL grounding system</li> <li>Current: 10A, Voltage: 250V, Cord</li> <li>Length: 1.83 Meters</li> <li>Outlet enclosures are made up of fireretadant materials, Maximum wattage: 2500W</li> </ul> <li>Presentation Clicker, Wireless</li> <li>Plug &amp; Play: no software to install, easy to use</li> <li>Long Distance Range: 15 meters long to use it</li> <li>Wave Length: 640~660nm (red light)</li> <li>Battery life (Presenter): 1050-hour maximum</li> <li>Battery life (Presenter): 1050-hour maximum</li> <li>Battery life (Presenter): 1050-hour maximum</li> <li>Mireless operating distance: Approx 10m</li> <li>1.49 in (37.8 mm) x 4.55 in (115.5 mm) x 1.08 in (27.4 mm)</li> <li>0.65 in (16.5 mm) x 2.31 in (58.6 mm) x 0.31 in (7.9 mm)</li> <li>Windows Vista, Windows 7, Windows 8</li> <li>Logitech® Wireless Presenter R400</li>					
9.       16       Units       • 6-gang universal outlet with individual switch       • Rigid brass strips for internal connection         9.       16       Units       • Impact resistant and highly conductive       • With REAL grounding system connection for safety       • With PEAL grounding system       1,102.50       17,640.00         9.       16       Units       • With PEAL grounding system connection for safety       • With built-in safety circuit breaker       • Current: 10A, Voltage: 250V, Cord Length: 1.83 Meters       • Outlet enclosures are made up of fire-retardant materials, Maximum wattage: 2500W         Presentation Clicker, Wireless       • Plug & Play: no software to install, easy to use       • Long Distance Range: 15 meters long to use it         9.       16       Units       • Wave Length: 640~660nm (red light)       • Battery life (Laser pointer): 20-hour maximum         • Battery life (Laser pointer): 1050-hour maximum       • Battery life (Presenter): 1050-hour maximum       • 623.50       9,976.00         • Wireless operating distance: Approx 10m       • Wireless operating distance: Approx 10m       • 0.31 in (7.9 mm)       • 0.31 in (7.9 mm)         • Windows Vista, Windows 7, Windows 8       Logitech® Wireless Presenter R400       • Windows 7       • 0.31 in (7.9 mm)			<ul> <li>Random color of black or white</li> </ul>		
9.16Units• Plug & Play: no software to install, easy to use • Long Distance Range: 15 meters long to use it • Wave Length: 640~660nm (red light) • Battery type: 2 AAA batteries • Battery life (Laser pointer): 20-hour maximum • Battery life (Presenter): 1050-hour maximum • Battery life (Presenter): 1050-hour maximum • Battery life (Presenter): 1050-hour maximum • Battery life (Nresenter): 1050-hour maximum • Battery life (Presenter): 1050-hour maximum • Wireless operating distance: Approx 10m 1.49 in (37.8 mm) x 4.55 in (115.5 mm) x 1.08 in (27.4 mm) 0.65 in (16.5 mm) x 2.31 in (58.6 mm) x 0.31 in (7.9 mm) • Windows Vista, Windows 7, Windows 8 Logitech® Wireless Presenter R400	8. 16	Units	<ul> <li>6-gang universal outlet with individual switch</li> <li>Rigid brass strips for internal connection</li> <li>Outlets are made of copper material for better grip</li> <li>Impact resistant and highly conductive</li> <li>With REAL grounding system connection for safety</li> <li>With built-in safety circuit breaker</li> <li>Current: 10A, Voltage: 250V, Cord Length: 1.83 Meters</li> <li>Outlet enclosures are made up of fire-retardant materials, Maximum wattage: 2500W</li> </ul>	1,102.50	17,640.00
guide"	9. 16	Units	<ul> <li>Plug &amp; Play: no software to install, easy to use</li> <li>Long Distance Range: 15 meters long to use it</li> <li>Wave Length: 640~660nm (red light)</li> <li>Battery type: 2 AAA batteries</li> <li>Battery life (Laser pointer): 20-hour maximum</li> <li>Battery life (Presenter): 1050-hour maximum</li> <li>Wireless operating distance: Approx 10m</li> <li>1.49 in (37.8 mm) x 4.55 in (115.5 mm) x</li> <li>1.08 in (27.4 mm)</li> <li>0.65 in (16.5 mm) x 2.31 in (58.6 mm) x</li> <li>0.31 in (7.9 mm)</li> <li>Windows Vista, Windows 7, Windows 8</li> <li>Logitech® Wireless Presenter R400</li> <li>Wireless mini-receiver with Quick start</li> </ul>	623.50	9,976.00

2. Delivery Period: \_\_\_\_\_ calendar days from the receipt of P.O.

3. Price quotations must be valid for a period of sixty (60) calendar days from date of submission and shall include all taxes, duties and/or levies payable. Bidders shall also indicate the brand and model of the items being offered.

- 4. Warranty shall be for a period of six (6) months for supplies and materials. Warranty for equipment must not be less than one (1) year from the date of acceptance and shall be accompanied with Warranty Certificate.
- 5. The quotation must be submitted to the Procurement Office through mail, fax or email at the contact details listed below **on or before 5:00 PM** of **March 5, 2024.**

Address	:	Procurement Office, Administration Building
		Cavite State University
		Indang, Cavite
E-mail	:	procurementoffice@cvsu.edu.ph / rfqmain@cvsu.edu.ph
Telefax	:	(046) 889-6373

6. The CvSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. CvSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

ROSELYN M. MARANAN

BAC Secretary, Goods and Consulting Services