








Republic of the Philippines  
**CAVITE STATE UNIVERSITY**  
 Don Severino de las Alas Campus  
 Indang, Cavite  
 cvsu.edu.ph



**SUPPLY, DELIVERY AND INSTALLATION OF VARIOUS EQUIPMENT FOR  
 INTERACTIVE DIGITAL CLASSROOM FOR CVSU-BACCOOR**

**ABC: ₱1,300,000.00**


Item No.	Quantity	Unit	Item Description	Pictures	Unit Cost	Total Cost
1	1	unit	<p><b>Terminal Device:</b> Intelligent Collaboration Device 86-inch infrared screen</p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- 86-inch D-LED touch screen</li> <li>- 4K60 resolution</li> <li>- Zero-gap bonding</li> <li>- anti-glare (AG)</li> <li>- Automatically adjusts screen brightness based on light sensing</li> <li>- Optical anti-blue light,</li> <li>- Typical contrast ratio: 1200:1</li> <li>- Typical brightness: 350 nits</li> <li>- Screen response time: 8ms</li> <li>- Touch accuracy: ±1mm</li> <li>- Immersive HD Intelligent Meetings</li> <li>- 1080p cloud meetings</li> <li>- 4K image sensor</li> <li>- Circulating heat dissipation design</li> <li>- Wi-Fi 6 for Direct Projection</li> <li>- Multiple projection modes for different scenarios</li> <li>- 16 ms ultra-low writing latency</li> <li>- Multiple pen thicknesses in full color</li> <li>- Multi-touch gestures</li> <li>- Handwriting recognition</li> <li>- Full-screen annotation</li> <li>- Remote bidirectional collaboration</li> <li>- Co-authoring</li> <li>- Multi-Window for efficient multitasking</li> <li>- Adjustable window ratio</li> <li>- Enterprise-level E2E security protection</li> <li>- HiBoard as a Welcome Page</li> <li>- with Customizable templates</li> </ul> <p><b>Inclusions:</b></p> <ul style="list-style-type: none"> <li>- Basic admin and hands-on training</li> <li>- Includes training manuals and certificates</li> <li>- 1 Year Email-, phone- and remote-based Support               <ul style="list-style-type: none"> <li>- Manufacturer's Certificate</li> <li>- Certificate of Distributorship</li> <li>- 1 year warranty for parts &amp; services</li> </ul> </li> </ul>		775,000.00	775,000.00


2	1	unit	<p>Compatible Rolling Stand for 86 inches Intelligent Collaboration Device</p>		29,000.00	29,000.00
3	1	unit	<p><b>Smart Collaboration Endpoint Accessories - OPS Module Requirements</b></p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Smart OPS</li> <li>- At least i5-10500, DDR4 8GB,128GB SSD</li> <li>- Windows10 IOT Enterprise</li> <li>- SAC,195mm,180mm,30mm,</li> </ul> <p><b>Interface:</b></p> <ul style="list-style-type: none"> <li>- Video out: 1 x HDMI 1.4, 1 x DP 1.2.</li> <li>- Audio in: 1 x 3.5mm.</li> <li>- Audio out: 1 x 3.5mm.</li> <li>- USB: 3 x USB Type-A 3.0, 3 x USB Type-A 2.0</li> <li>- Windows 10 enterprise operate System</li> <li>- 1 year warranty</li> </ul>		92,000.00	92,000.00
4	1	unit	<p>- Compatible with Intelligent Collaboration Device</p> <p><b>Digital signal processing (Sound System Mixer)</b></p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Industrial embedded architecture. Embedded design. Stable and reliable</li> <li>- USB and analog interface</li> <li>- Integrated automatic noise suppression technology</li> <li>- 6-way microphone input; software 48V phantom power</li> <li>- 3-channel mono line-in input : 3.5mm interface and terminal double backup</li> <li>- 3-channel mono line-out output; 3.5mm interface and terminal double backup</li> <li>- 6 balanced inputs with 16 EQ segments</li> <li>- Intelligent mixing function Function</li> <li>- Reduce reverberation</li> <li>- With one key debugging Function</li> <li>- Echo cancellation; Echo processing delay ability: 128ms, 256ms, 512ms</li> <li>- Built in no less than two USB interfaces and one network</li> </ul>		16,000.00	16,000.00


			<p>interface</p> <ul style="list-style-type: none"> <li>- Environmental sound field detection; Background noise, STI, C5015. Echo rejection ratio : &gt;60dB</li> <li>- Sampling rate : 48K</li> <li>- 1 year warranty</li> </ul>			
5	6	pcs	<p><b>Ceiling Microphones:</b></p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Frequency response: 100Hz~18KHz</li> <li>- Sensitivity: -40dB±3 dB (re 0dB=1V/Pa@1kHz)</li> <li>- Pointing characteristics: Ultra-Cardioid ≤135°</li> <li>- Output impedance: 200Ω±30%</li> <li>- Output amplitude: Max 300mV</li> <li>- Maximum withstand sound pressure: 110dB SPL</li> <li>- Dynamic range: 76dB (A)</li> <li>- Signal to noise ratio: 60dB (A) (re 94dB SPL=1Pa@1KHz)</li> <li>- Power Supply: DC48V</li> <li>- Output connector: XLR-3-12C</li> <li>- 1 year warranty</li> </ul>		6,000.00	36,000.00
6	2	pcs	<p><b>Sound Box</b></p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Loudspeaker: 4.5" (4Ω) Sub</li> <li>- Box sensitivity:(1m@2V) 87Db</li> <li>- Frequency Response: 80Hz~18KHz</li> <li>- Rated power: 30W</li> <li>- output power: L: 15W R: 15W</li> <li>- Total harmonic distortion: L: 0.25% R: 0.25%</li> <li>- Input sensitivity: 700mV</li> <li>- Signal to noise ratio: 74dB (power : 1W/4Ω)</li> <li>- Input interface: red (+), black (-)</li> <li>- Speaker weight: (Two) 5.8kg max</li> <li>- 1 year warranty</li> </ul>		6,500.00	13,000.00
7	2	sets	<p><b>Digital Board 86-inch (2,200 mm x 350 mm x 200mm)</b></p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Touch resolution: 32768*32768/4096*4096</li> <li>- Accuracy: ≤2mm</li> <li>- Interface: Support USB2.0/USB3.0</li> <li>- Waterproof / dustproof: ≥IP55</li> <li>- Work temperature: -10°C~45°C</li> <li>- Work humidity: 0%-90%</li> <li>- Work voltage DC: 4.6V-DC 5V</li> <li>- Power consumption: &lt;1W (200mA at 5V)</li> <li>- Gesture response: Eraser or</li> </ul>		48,000.00	96,000.00

			<p>cloth clean the board surface, digital mark also can be cleaned</p> <ul style="list-style-type: none"> <li>- Display delay: Digital board writing display on the IFPD <math>\leq 120\text{ms}</math></li> <li>- File save: Support digital board writing local save and share via QR code</li> <li>- Hotkey icons: Must have preview, page up, page down, red, white, yellow pens, save, vote, screen clean functions.</li> <li>- Interactivity: Digital board and IFPD support; support interactive work; can display on the IFPD</li> <li>- Writing mode: Software support single board writing display on the full screen; dual boards display on the same screen; can save the writing contents as original display ratio.</li> <li>- 1 year warranty</li> </ul>			
8	200	pcs	<p>Acoustic Panels</p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Single foam panel</li> <li>- Dimension: 30cm (l) x 30 (w) x 5cm (thickness)</li> <li>- Color: Black</li> <li>- Can be used to absorb unwanted noise dampening, providing moderate sound absorption</li> <li>- Great for studios, recording studios, control rooms, home entertainment rooms, home theaters, office and more</li> <li>- With installation</li> <li>- 1 year warranty</li> </ul>		450.00	90,000.00
9	1	unit	<p>55-inch LED Monitor</p> <p><b>Specifications:</b></p> <p><b>SPECIAL FEATURES</b></p> <ul style="list-style-type: none"> <li>- Smart TV: Yes</li> <li>- Operating System &amp; Version: Android 10.0</li> <li>- CPU: Quad Core</li> <li>- GPU: Mali-G52</li> <li>- Internal Memory: 8GB</li> <li>- RAM: 2GB</li> <li>- Voice Search: Yes</li> <li>- Google Assistant: Yes</li> <li>- Wireless Display</li> <li>- Bluetooth: 5.0 (Input &amp; Output)</li> <li>- Time Shift: Yes</li> <li>- Wifi Connectivity: 2.4G+5G</li> <li>- USB Media File Playback: Photo, Video, Music, Text (HEVC)</li> <li>- Open Browser: Yes</li> </ul>		45,000.00	45,000.00



			<p><b>VIDEO</b></p> <ul style="list-style-type: none"> <li>- Backlight Type: Direct Led</li> <li>- Panel Type: IPS</li> <li>-</li> <li>- Display Resolution: UHD 3840 x 2160</li> <li>- Viewing Angle: 178 Degree</li> </ul> <p>- Refresh frequency: 50/60Hz</p> <p><b>AUDIO</b></p> <ul style="list-style-type: none"> <li>- Speaker Type: Down Firing</li> <li>- Surround: Yes</li> <li>- Equalizer: Yes</li> <li>- DTS Studio Sound: Yes</li> <li>- Dolby Digital (Decoder): Yes</li> <li>- Dolby Digital plus (Decoder): Yes</li> <li>-</li> <li>- Audio Power Output (L+R) (rms): 10w + 10w</li> </ul> <p><b>DESIGN</b></p> <ul style="list-style-type: none"> <li>- Finish: Glossy</li> <li>- Color: Black</li> <li>- Stand Base: Metal</li> <li>- Bezel Type: Borderless Design</li> </ul> <p><b>TERMINALS</b></p> <ul style="list-style-type: none"> <li>- USB Ports: 2(2.0)</li> <li>- HDMI Ports: 3(2.0)</li> <li>- Ethernet: 1</li> <li>- RF In: Cable &amp; Air</li> <li>- AV In: 1(3.5mm)</li> <li>- Digital Output: 1(Optical)</li> </ul> <p><b>POWER</b></p> <ul style="list-style-type: none"> <li>- Working Voltage: 100-240v/ 50-60Hz</li> <li>- Rated Power Consumption: 200W</li> <li>- 1 year warranty</li> </ul>			
10	2	units	<p>Student and Teachers Camera (4K Classroom Auto Tracking Camera)</p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- 4K Classroom Auto Tracking Camera</li> <li>- Sensor: 1/2.8 inches, CMOS</li> <li>- Effective Pixels: 8.46 Megapixels</li> <li>- Scanning Module: Progressive</li> <li>- Type of Lens Mount: M12</li> <li>- Focal length: f=2.8mm,</li> <li>- Horizontal FOV: 95°,</li> <li>- Minimum illumination: 0.5 Lux @ (F1.8, AGC ON)</li> <li>- Shutter Speed: 1/30s ~ 1/10000s</li> <li>- White Balance: Auto, Indoor,</li> </ul>		45,000.00	90,000.00

			<p>Outdoor, One Push, Manual, VAR</p> <ul style="list-style-type: none"> <li>- Digital Noise Reduction: 2D, 3D</li> <li>- PoE: Support</li> <li>- HD Output: 1x 3G-SDI: BNC, 800mVp-p, 75Ω, as per SMPTE 424M standard, PoC supported</li> <li>- Network Interface: 1x RJ45: 10M/100M adaptive Ethernet PoE support</li> <li>- USB Interface: 1x USB2.0: A type socket,</li> <li>- Audio Interface: 1x LINE IN: 3-core phoenix interface</li> <li>- Control Interface: 1x RS485: 2-core phoenix interface, Max. distance 1200m, VISCA/Pelco-D/Pelco-P protocols</li> </ul> <p>NETWORK FEATURES)</p> <ul style="list-style-type: none"> <li>- Video Compression: H.264 / MJPEG</li> <li>- Video Stream: First Stream, Second Stream</li> <li>- 1 year warranty</li> </ul>			
11	1	unit	<p>Uninterruptible power supply (UPS)</p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Capacity: 1000VA/600W</li> <li>- Nominal Input Voltage: 220/230/240V</li> <li>- Operating Voltage Range: 140-300V</li> <li>- Operating Frequency Range: 50/60Hz +/- 10%</li> <li>- Output Voltage Range: <ul style="list-style-type: none"> <li>• Battery Mode: 220/230/240, Simulated Sine Wave at Nominal Voltage +/- 10%,</li> <li>• Utility Mode: 220/230/240V, Sine Wave at Nominal Voltage +/- 10%,</li> </ul> </li> <li>- Frequency Range: <ul style="list-style-type: none"> <li>• Battery Mode: 50 or 60Hz +/- 1Hz, Utility Mode: 50/60Hz +/- 10% (auto-sense),</li> </ul> </li> <li>- Transfer Time: Typical 2 to 6ms.</li> <li>- Output Socket: 4 x Universal Type (Surge Protected &amp; Battery Back-up)</li> <li>- Battery Type: Maintenance-Free, Sealed Lead Acid, Leak Proof</li> <li>- Typical Recharge Time: 4 to 6 Hours up to 90% capacity, Back-up Time: At least 15 minutes</li> </ul>		15,000.00	15,000.00

			<ul style="list-style-type: none"> <li>- Protection: Discharge, Overcharge, Overload &amp; Surge Protect,</li> <li>- with Alarm: Battery Mode: Sounding every 10 seconds, Low Battery: Sounding every second, Overload: Sounding every 0.5 Second</li> <li>- 1 year warranty</li> </ul>			
12	2	pcs	<p>Wall Mount Bracket of Box Camera</p> <p><b>Specifications:</b></p> <ul style="list-style-type: none"> <li>- Variable angle camera mount</li> <li>- Compatible with Box Cameras and Auto-Tracking Camera</li> <li>- Color: White</li> </ul>		1,500.00	3,000.00
<b>TOTAL</b>						<b>1,300,000.00</b>