

Republic of the Philippines CAVITE STATE UNIVERSITY Don Severino de las Alas Campus

Indang, Cavite, Philippines *(a46) 889-6373*

www.cvsu.edu.ph

INVITATION TO SUBMIT QUOTATION Supply and Delivery of Various Electrical, Tools, Supplies and Equipment for CvSU Carmona Campus

1. The Cavite State University (CvSU) invites interested firms/supplier to submit quotation for the project "Supply and Delivery of Various Electrical, Tools, Supplies and Equipment for CvSU Carmona Campus" with an Approved Budget for the Contract (ABC) of Three Hundred Eighty-Four Thousand Eight Hundred Sixty Pesos and 64/100 Only (PhP 384,860.64). Quotation received in excess of the ABC shall be automatically rejected at the opening.

Item No.	Unit	Description	Quantity	Unit Cost	Total Cost
1.	рс	Crimping Tool, Self-Adjusting Wire Stripper, 8-InchStrip wire from 10-24 AWG Adjustable stopper controls the length of the core strip Wire crimper crimps 10-22 AWG insulated, 10-22 AWG non-insulated and 7-9mm Comfortable high-leverage handles	5	800.00	4,000.00
2.	pair	CUTTER PLIERS, HD, Miniature Basic Diagonal Cutting Pliers 4", Nickel chromed for durability, Double dip handles for comfort	25	170.00	4,250.00
3.	unit	DRIVER DRILL, CORDLESS, HD, 13mm 20V Max Brushless Cordless Hammer Drill Driver set with FREE Magnetic PH2 Screw Bit with Battery pack and charger included	2	11,025.00	22,050.00
4.	рс	FLAT SCREW DRIVER SET 8's, Phillips - PH075xMM PH1x75MM. PH2x38MM. PH2x100MM, Tip identification on handles for easy selection Flat - 3x75MM .5x75MM 6x38MM 6x100MM, Chrome- plated bars for corrosion resistance, Magnetic tips for secure grip on fasteners, Black oxide tips for precise fit into fasteners, Smooth-domed end for fast spinning action, Bi-material handle for comfort and control	30	717.00	21,510.00
5.	unit	FLOOR POLISHER, 10" Premier Low Speed Polisher, 1/4HP, 190RPM, 220V, Off-set gear, Aluminum Deck, Gear release handle, 15mtrs. Long cable	1	30,000.00	30,000.00
6.	рс	SOLDERING FLUX, 10ML	5	100.00	500.00
7.	unit	HAND TROLLEY CART, FLATFORM TYPE, 150 KGS, Steel wheeled platform truck folds and opens in seconds, Tubing and platform made of tough steel for added durability, Strong, rigid, steel	3	4,135.00	12,405.00

		handle for secure manoeuvering of loads, 4 ball bearing braked wheels for easy and safe steering, Compact design for easy storage, Steel Base Plate 72.5cm x 47cm, Total Height (Incl Handle) 82cm, Open Dimensions 72,5 x			
8.	pair	47 x 82 cm LONG NOSE PLIERS, HD, Made of forged steel, Nickel plated finish, Two tone soft plastic grips, With grip ridges on the jaws, Has a wire side cutting blades, Made of forged steel, PVC anti-slip handles, Size: 6in or 160mm, Weight: 5oz or 155g	30	270.00	8,100.00
9.	рс	Mini Electric Drill 12VDC, Clamping range: 0.5-3.2MM, Speed range: 18000r/min, Input voltage: 100-240V, Output voltage: 12V, Power: 13W, Body size: 155x27mm for PCB (Electronics)	20	400.00	8,000.00
10.	unit	Mobile TV Stand HD, Material: Cold rolled steel, Size: Total L*H*W 24*15.7*50in, TV Mount Height Adjustment: 42.5"-59", Shelf size: 8.6*11.5 inches, Bottom shelf: 24*15.7 inches, Weight: 13kg, Adjustment Angle: Tilt -15°~ +15°, TV Weight Capacity: 66lbs, Fits TV Screen Size Up To: 32"-65" TV screen, 100 x 100, 200 x 100, 200 x 200, 300X200, 400 x 300, 400 x 400, 500 x 400, 600 x 400, HD Cable: Length 5.9ft, All four wheels can be locked	6	3,024.27	18,145.64
11.	рс	PHILIP SCREW SET, Magnetic Screw Driver Philip & Flat Rubber Handle 4inch, 6inch, 8inch	30	470.00	14,100.00
12.	unit	Crimping Tools, Multipurpose 12" HD, Heavy duty tool for industrial or commercial work environment	10	772.00	7,720.00
13.	pair	PLIERS, Combination pliers size: 7inch or 180mm, Long nose pliers size: 6inch or 160mm, Diagonal cutting pliers size: 6inch or 160mm	30	221.00	6,630.00
14.	unit	PRESSURE WATER SPRAYER, 1.5HP Induction type electric motor, suitable use for Commercial and Agri-Industrial purposes, The sprayer hose of this kind can be extended up to 300-meters length, Max operating pressure of 450psi for single user; while 750psi for two users, Water volume of 20 liters/minute, this will surely get the job done efficiently	2	7,500.00	15,000.00
15.	рс	SCREW DRIVER, w/ Rubber Handle For Safe And Comfortable Handling~Item Inclusion, Magnetic Screw 8" Chrome + 4" Handle = 12", Magnetic Philip Screw Driver 12" / Xlw Magnetic Cross Screw	30	185.00	5,550.00

16. pc Iron Length: 20-21 cm, Cable Length: 150 cm, Working Voltage: 220V 50-60HZ, 60watts 17. pc Soldering pump, Suction capacity: 35cm-Hg, Whole Length: 210mm, 18. pc Soldering pump, Suction capacity: 35cm-Hg, Whole Length: 210mm, 19. vo			Driver 12" Chrome Vanadiumdurable Tools,			
17.	16.	рс	SOLDERING IRON 60WATTS, Soldering Iron Length: 20-21 cm, Cable Length: 150 cm, Working Voltage: 220V 50-	60	150.00	9,000.00
18. pc Soldering pump, Suction capacity: 35cm-Hg, Whole Length: 210mm, VOM Multitester (Analog), Analogue meter featuring null (zero centre) capability, Drop/Shock proof taut band movement, Null meter facility: ±5/±2/5 19. pc Vdc, Resistance measurement up to 20 2,320.00 46,400.00 19. pc Vdc, Resistance measurement up to 20 2,320.00 46,400.00 19. pc Vdc, Resistance measurement up to 20 2,320.00 46,400.00 10. pc Teste leads conveniently store in case, Size 129 x 160 x 42mm, weight approx 320g VOM Multitester (Digital), Low power ohm (input voltage 0.4V) at continuity range, AC frequency bandwidth: 40 ~ 400Hz, 3-3 / 4 digits 4000 count WELDING MACHINE, Portable with welding mask, Power Voltage: 220V/ 60Hz, Max. Input Power: 9, Efficiency: 85, Max. No Load Voltage: 65, Current Range: 10-300A, Duty Cycle: 60%, Usable Electrodes: 1.6-5mm Wire Stripper (HD), Stripping wires range: 10/AWG-24AWG (0.2-6mm^2), Crimping functions: Crimp the insulated terminals: 0.5-6mm^2 (14-, 22 AWG), Crimp the non-insulated terminals: 0.5-6mm^2 (14-, 22 AWG), Crimp the insulated terminals: 0.5-6mm^2 (14-, 22 AWG), Crimp the spinition terminals: 7-8mm/2 ANGLE GRINDER, Power Input: 850 W, Max. Disc Diameter: 100 mm, No Load Speed: 12000 rpm, Spindle Thread: M10, Weight: 1.75 kg, Length(with disc): 296 mm, Height 57: mm Cable Marking Printer (LCD Display) with accessories, Printing method Thermal transfer, Resolution 300dpi, Printing speed Tubes: High 25 mm/s, Standard 18.5 mm/s, Low 12.5 mm/s, Labels: 25	17.	рс	•	10	200.00	2,000.00
VOM Multitester (Analog), Analogue meter featuring null (zero centre) capability, Drop/Shock proof taut band movement, Null meter facility: ±5/±25	18.	рс	Soldering pump, Suction capacity: 35cm-	20		6,000.00
20. pc ohm (input voltage 0.4V) at continuity range, AC frequency bandwidth: 40~ 400Hz, 3-3 / 4 digits 4000 count 20 2,760.00 55,200.00 50,200.00 60Hz, Albert Portable With Welding mask, Power Voltage: 220V/60.00 60Hz, Albert Portable With Portable With Portable With Portable With Portable With Portable St. Power Input	19.	рс	VOM Multitester (Analog), Analogue meter featuring null (zero centre) capability, Drop/Shock proof taut band movement, Null meter facility: ±5/±25 Vdc, Resistance measurement up to 200MΩ, Capacitance measurement up to 10μF, Test leads conveniently store in case, Size 129 x 160 x 42mm, weight approx 320g	20	2,320.00	46,400.00
Welding mask, Power Voltage: 220V/ 60Hz, Max. Input Power: 9, Efficiency: 85, Max. No Load Voltage: 65, Current Range: 10-300A, Duty Cycle: 60%, Usable Electrodes: 1.6-5mm	20.	рс	ohm (input voltage 0.4V) at continuity range, AC frequency bandwidth: 40~	20	2,760.00	55,200.00
range:10/AWG-24AWG (0.2-6mm^2), Crimping functions: Crimp the insulated terminals: 0.5-6mm^2 (10-22 AWG), Crimp the non-insulated terminals: 0.5- 6mm^2 (4-, 22 AWG), Crimp the ignition terminals: 7-8mm^2 ANGLE GRINDER, Power Input: 850 W, Max. Disc Diameter: 100 mm, No Load 23. pc Speed: 12000 rpm, Spindle Thread: M10, Weight: 1.75 kg, Length(with disc): 296 mm, Height 57: mm Cable Marking Printer (LCD Display) with accessories, Printing method Thermal transfer, Resolution 300dpi, Printing speed Tubes: High 25 mm/s, Standard 18.5 mm/s, Low 12.5 mm/s, Labels: 25	21.	unit	welding mask, Power Voltage: 220V/ 60Hz, Max. Input Power: 9, Efficiency: 85, Max. No Load Voltage: 65, Current Range: 10-300A, Duty Cycle: 60%,	5	8,300.00	41,500.00
Max. Disc Diameter: 100 mm, No Load Speed: 12000 rpm, Spindle Thread: M10, Weight: 1.75 kg, Length(with disc): 296 mm, Height 57: mm Cable Marking Printer (LCD Display) with accessories, Printing method Thermal transfer, Resolution 300dpi, Printing speed Tubes: High 25 mm/s, Standard 18.5 mm/s, Low 12.5 mm/s, Labels: 25	22.	рс	range:10/AWG-24AWG (0.2-6mm^2), Crimping functions: Crimp the insulated terminals: 0.5-6mm^2 (10-22 AWG), Crimp the non-insulated terminals: 0.5- 6mm^2 (4-, 22 AWG), Crimp the ignition	10	800.00	8,000.00
accessories, Printing method Thermal transfer, Resolution 300dpi, Printing speed Tubes: High 25 mm/s, Standard 18.5 mm/s, Low 12.5 mm/s, Labels: 25	23.	рс	Max. Disc Diameter: 100 mm, No Load Speed: 12000 rpm, Spindle Thread: M10, Weight: 1.75 kg, Length(with disc): 296	3	5,600.00	16,800.00
Low 12.5 mm/s Output rate High Mode:	24.	unit	accessories, Printing method Thermal transfer, Resolution 300dpi, Printing speed Tubes: High 25 mm/s, Standard 18.5 mm/s, Low 12.5 mm/s, Labels: 25 mm/s, Labels: High 25 mm/s, Standard / Low 12.5 mm/s, Output rate High Mode: 35 pcs./min., Standard Mode: 30 pcs./min., Low Mode: 21 pcs./min., (Printing 20mm tubes, 5 full-size characters, consecutive print mode, half-cutting.), Power supply Exclusive AC Adapter (Input voltage: AC 100V - 240V	1	22,000.00	22,000.00
			00 / 00 FIZ)	TOT	AL AMOUNT	384,860.64

- 3. Price quotations must be valid for a period of sixty (60) calendar days from date of submission and shall include all taxes, duties and/or levies payable. Bidders shall also indicate the brand and model of the items being offered.
- 4. Warranty shall be for a period of six (6) months for supplies and materials. Warranty for equipment must not be less than one (1) year from the date of acceptance and shall be accompanied with Warranty Certificate.
- 5. The quotation must be submitted to the Procurement Office through mail, fax or email at the contact details listed below **on or before 5:00 PM** of **December 16, 2024.**

Address : Procurement Office, Administration Building

Cavite State University

Indang, Cavite

E-mail : procurementoffice@cvsu.edu.ph / rfqmain@cvsu.edu.ph

Telefax : (046) 889-6373

6. The CvSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. CvSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

ROSELYN M. MARANAN

BAC Secretary, Goods and Consulting Services