

Republic of the Philippines **CAVITE STATE UNIVERSITY Don Severino de las Alas Campus** Indang, Cavite, Philippines (046) 889-6373 www.cvsu.edu.ph

INVITATION TO SUBMIT QUOTATION Supply and Delivery of Laboratory Equipment for BEAN 3 BARAKO OMICS PROJECT

 The Cavite State University (CvSU) invites interested firms/supplier to submit quotation for the project "Supply and Delivery of Laboratory Equipment for BEAN 3 BARAKO OMICS PROJECT" with an Approved Budget for the Contract (ABC) of One Hundred Sixty-Five Thousand Pesos Only (PhP 165,000.00). Quotation received in excess of the ABC shall be automatically rejected at the opening.

ltem No.	Unit	Description	Quantity	Unit Cost	Total Cost
1.	Unit	 MICROWAVE OVEN a. Product Overview: Power Defrost, Rotating ceramic plate inside, Counter top, Quick 30 sec. function, Easy to see LCD Screen, Compact b. Specifications Capacity: 30.0L to 32.0L Microwave Type: Countertop Control Type: Electronic Touch LED Power Levels: 7 to 10 Turntable Size: 11 to 13 in Net Weight: ~35.0 lb. Cavity Dimensions (WxHxD): ~16 x 12 x 16 (Required: can contain an Upright 350 mL ketchup bottle) Overall Dimensions (WxHxD): ~20 x 16 x 20in Inclusions: Instruction manual, basic cleaning kit, rotating ceramic plate Warranty: 1 to 2 years Others: With light inside while the food/material is being heated Delivery: 30 days upon receipt of Purchase Order 	1	15,000.00	15,000.00
2.	Pcs	REFRIGERATORS: TWO (2) CHILLERS & ONE (1) KITCHEN REF A. CHILLER (2 UNITS) a. Product Overview: 7-level Temperature Control, Double Glass Door, Fan-cooled System, Internal Lamp, Lighted Panel, 3 to 4 Adjustable Coated Wire Shelves, Recessed Handle, Key Lock, Adjustable Levelling Feet, 167W Input Power b. General Specifications • Temperature Range: 0°C to 15°C	3	23,333.33	70,000.00

 Type : Inverter Showcase Chiller Capacity, Fresh Food: 200 to 250 liters 8 to 12 cu.ft. Defrost System: Manual No. of Fresh Food Shelves : 3 wire shelves Refrigerator Light: LED Insulation: Cyclopentane Power Requirements: 220v / 60Hz Door : Glass, see through Weight: ~70kg Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
8 to 12 cu.ft. • Defrost System: Manual • No. of Fresh Food Shelves : 3 wire shelves • Refrigerator Light: LED • Insulation: Cyclopentane • Power Requirements: 220v / 60Hz • Door : Glass, see through • Weight: ~70kg • Dimensions: ~ 530 x 1800 x 580mm • Power Requirements: 220v / 60Hz • Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR • Warranty: 1 to 5 years • Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications • Temperature Range (freezer): -5°C to	
 Defrost System: Manual No. of Fresh Food Shelves : 3 wire shelves Refrigerator Light: LED Insulation: Cyclopentane Power Requirements: 220v / 60Hz Door : Glass, see through Weight: ~70kg Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 No. of Fresh Food Shelves : 3 wire shelves Refrigerator Light: LED Insulation: Cyclopentane Power Requirements: 220v / 60Hz Door : Glass, see through Weight: ~70kg Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
shelves • Refrigerator Light: LED • Insulation: Cyclopentane • Power Requirements: 220v / 60Hz • Door : Glass, see through • Weight: ~70kg • Dimensions: ~ 530 x 1800 x 580mm • Power Requirements: 220v / 60Hz • Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR • Warranty: 1 to 5 years • Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications • Temperature Range (freezer): -5°C to	
 Refrigerator Light: LED Insulation: Cyclopentane Power Requirements: 220v / 60Hz Door: Glass, see through Weight: ~70kg Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Insulation: Cyclopentane Power Requirements: 220v / 60Hz Door : Glass, see through Weight: ~70kg Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Power Requirements: 220v / 60Hz Door : Glass, see through Weight: ~70kg Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Door : Glass, see through Weight: ~70kg Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Weight: ~70kg Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Dimensions: ~ 530 x 1800 x 580mm Power Requirements: 220v / 60Hz Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Inclusions: Manual, key, refrigerator support stand (with wheels, heavy duty, & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
support stand (with wheels, heavy duty, & adjustable) and AVR • Warranty: 1 to 5 years • Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications • Temperature Range (freezer): -5°C to	
 & adjustable) and AVR Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Warranty: 1 to 5 years Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 Delivery: 30 days upon receipt of Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
Purchase Order B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications • Temperature Range (freezer): -5°C to	
 B. KITCHEN REFRIGERATOR (1 UNIT) a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
 a. Product Overview: Has antibacterial Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications Temperature Range (freezer): -5°C to 	
Property to keep stored products fresh, Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications • Temperature Range (freezer): -5°C to	
Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications • Temperature Range (freezer): -5°C to	
Digital Inverter, Easy slide shelf, rust and stain resistant textured body b. General Specifications • Temperature Range (freezer): -5°C to	
stain resistant textured body b. General Specifications ● Temperature Range (freezer): -5°C to	
• Temperature Range (freezer): -5°C to	
3°C	
 Temperature Range: 0°C to 15°C 	
Capacity: 10cuft. to 14 cuft	
Type: 2 Door Bottom Freezer No Frost	
Inverter	
Smart Function: Yes	
Capacity, Freezer: 80 to 90.0 L	
Capacity, Fresh Food: 200.0 to 220.0 L	
• Capacity, Total Shelf Area: 250.0 to	
300.0 L	
Defrost System: Automatic	
Temperature Control: Touch Button	
Panel	
Fresh Food Shelves: 2 to 3	
Adjustable Door Shelves: 2 to 3	
Adjustable Fresh Food Shelves: 2 to 3	
Crisper Shelf: 1 to 2	
• Freezer Shelves: ~2	
 Door Shelves – Fresh Food: 3 	
 Door Shelves – Freezer: 1 	
Refrigerator Light: LED	
Insulation: Cyclopentane	
• Dimensions: ~600mm x 1900mm x	
700mm	
Weight: 50 to 65kg	
Power Requirements: 220 – 240V	

		• Inclusions: Instruction material, AVR,		
		refrigerator support stand		
		Warranty: 1 to 3 years		
		• Delivery: 30 days upon receipt of		
		Purchase Order		
		MINI CENTRIFUGE		
		a. Product Overview: Benchtop		
		centrifuge, 300 RPM to 20,000 RPM,		
		Intuitive control, easy to read display,		
		one click lid closure		
		b. Specifications		
		 Used with standard 1.0, 1.5, 2.0 mL 		
		tubes and 0.2 mL PCR tubes		
		 Approximately 12 x 1.5/2.0/0.2 mL 		
		capacity in one cycle or better		
		 At least 2.5% speed deviation and 		
		~16,500G centrifugal acceleration		
		 7 Segment LED timer display 		
		 Duration is adjusted from seconds to 		
		minutes (0.1 to 100 mins.)		
		• Centrifuge RPM can be adjusted from		
		300-20,000 RPM or better		
		• Temperature can be adjusted from 4°C		
		to 40°C		
		• Dimensions (W x H x D): ~200 x 150 x		
		300 mm		
		 Approximately 4.0 kgs in weight 		
		• Interface: USB		
3.	Pc	Unbalance Sensor: Yes		
0.	10	Quick Stop: Yes		
		Protective Cover: Yes		
		• Voltage & Frequency: 220–230V,		
		50/60 Hz		
		Permissible Relative: at least 80%		
		Humidity		
		Rotor Exchange: without tool		
		Easily transferred or placed from one		
		place to another		
		One-click or automatic cover/lid		
		opening		
		 Internal lid for sealing the 		
		microcentrifuges facilitate vacuum		
		sealing		
		 Acceleration, centrifugation, and 		
		deceleration can be adjusted		
		Have sound and light indicator once		
		the cycle has started and has finished		
		Has sound and light indicator or		
		warning if the external lid had not been		
		closed properly		
		 Retains the settings utilized from 		
		previous usage		
		 Heavy duty and user-friendly 		
	1	- Houry duty and door-mondry	I	

	тот	AL AMOUNT	165,000.00
of the proper handling and usage of the product is provided before acceptance.			
Presentation or demonstration (on-site)			
Purchase Order			
• Delivery: 30 days upon receipt of			
• Warranty: 2 to 3 years			
(6pcs/set)			
adapters for 0.2 mL PCR tubes			
strips, 8 x 0.2 mL tubes, and Two (2) sets			
attachment with capacity of 2 x PCR			
 Inclusions: One (1) PCR set 			

- 2. Delivery Period: _____ calendar days from the receipt of P.O.
- 3. Price quotations must be valid for a period of sixty (60) calendar days from date of submission and shall include all taxes, duties and/or levies payable. Bidders shall also indicate the brand and model of the items being offered.
- 4. Warranty shall be for a period of six (6) months for supplies and materials. Warranty for equipment must not be less than one (1) year from the date of acceptance and shall be accompanied with Warranty Certificate.
- 5. The quotation must be submitted to the Procurement Office through mail, fax or email at the contact details listed below **on or before 5:00 PM** of **February 20, 2025.**

Address	:	Procurement Office, Administration Building
		Cavite State University
		Indang, Cavite
E-mail	:	procurementoffice@cvsu.edu.ph / rfqmain@cvsu.edu.ph
Telefax	:	(046) 889-6373

6. The CvSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. CvSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

ROSELYN M. MARANAN BAC Secretary, Goods and Consulting Services