
GENERAL NOTES AND SPECIFICATIONS:

- ALL WORK HEREIN SHALL BE DONE IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS.
- 2. ELECTRICAL WORKS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE PHILIPPINE ELECTRICAL CODE, MUNICIPAL/CITY LAWS AND ORDINANCES AND THE REGULATIONS FO THE LOCAL POWER AND TELEPHONE COMPANY.
- 3. THE JOB SHALL BE EXECUTED IN THE MOST THOROUGH PROMPT AND WORKMANLIKE MANNER EMPLOYING STANDARD TOOLS, EQUIPMENT, METHODS AND GOOD ENGINEERING PRACTICE. THE JOB SHALL BE DONE IN ALL ASPECTS AS REQUIRED PER PLANS AND SPECIFICATIONS AND READY FOR OPERATION.
- 4. THE DRAWINGS AND SPECIFICATIONS ARE INTENDED TO PERSENT A GENERAL LAYOUT AND BROAD OUTLINE/DESCRIPTION OF THE PROJECT, BUT DO NOT NECESSARILY INDICATE OR DESCRIBE ACTUAL LOCATIONS, LEVELS AND DISTANCES OF THE EQUIPMENT. THE CONTRACTOR IS HEREBY REQUIRED TO MAKE SUCH ADJUSTMENTS AT THE JOBSITE THAT ARE GOVERNED BY ACTUAL FIELD CONDITION.
- 5. SERVICE VOLTAGE TO THE BUILDING FROM THE POWER SOURCE SHALL BE 230V.
- 6. SERVICE ENTRANCE WIRING SHALL BE RIGID STEEL CONDUIT (RSC).
- 7. FEEDER WIRING SHALL BE ELECTRICAL METALLIC TUBING (EMT).
- 8. BRANCH CIRCUIT WIRING ELECTRICAL METALLIC TUBING (EMT).
- 9. BRANCH CIRCUIT WIRING EMBEDDED IN CONCRETE SHALL BE IN PVC PIPE WITH ADEQUATE GROUND WIRE FOR EQUIPMENT GROUNDING.
- 10. LIGHT SWITCHES SHALL BE 15A, 230VAC.
- 11. ALL MATERIALS SHALL BE BRAND NEW AND OF APPROVED TYPE FOR LOCATION AND PURPOSE INTENDED.
- 12. DEVICES, FIXTURES LOCATED OUTDOOR SHALL BE WEATHERPROOF TYPE.
- 13. MOUNTING HEIGHTS ARE:
 - A. LIGHT SWITCHES
 - B. CONVENIENCE OUTLETS
 - C. COUNTER TOP C.O,
 - D. TELEPHONE OUTLETS
 E. PANEL BOARD
 - F. EMERGENCY LIGHT


- 1.40M ABOVE FLOOR FINISH
- 0.30M ABOVE FLOOR FINISH
- 0.40M TO .50M ABOVE THE COUNTER
- 0.30M ABOVE FLOOR FINISH
- 1.50M ABOVE FLOOR FINISH
- 0.30M BELOW CEILING LINE
- 14. ANY DISCREPANCY BETWEEN THE PLANS AND SPECIFICATIONS SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER FOR CLARIFICATION OR DECISION.
- 15. THE ENTIRE WORK SHALL BE DONE UNDER THE DIRECT SUPERVISION OF DULY REGISTERED ELECTRICAL ENGINEER.
- 16. REFER TO SHEET E-2 FOR EXACT NUMBER AND LOCATION OF DEVICES/EQUIPMENT FOR ELECTRICAL SYSTEM. ANY CONFLICT ON QUANTITY AND/OR LAYOUT MUST BE VERIFIED AND CONFIRMED TO DESIGNER/CONSULTANT.
- 17. REFER TO LOAD SCHEDULE FOR THE RATING OF INDIVIDUAL ENCL, ACB'S IN NEMA-3R.
- 18. ALL ELECTRICAL CONDUITS AND TELEPHONE SERVICE ENTRANCE THAT INSTALLED BELOW THE GROUND SHALL BE IN CONCRETE ENCASEMENT.
- 19. ANY DEVICES OR EQUIPMENT NOT REFLECTED OR SHOWN ON PLANS BUT REQUIRED TO COMPLETE THE SYSTEM MUST BE INCLUDED ON SCOPE OF WORK.
- 20. REQUEST FOR TEMPORARY POWER INTERRUPTION SHOULD BE COORDINATED TO OWNER'S REPRESENTATIVE OR DESIGNER.
- 21. THE SIZE OF GENERATOR IS 40% OF THE TOTAL VA LOAD. THIS IS INTENDED TO SUPPLY ELECTRIC POWER FOR LIGHTINGS AND OTHER IMPORTANT APPLIANCES DURING THE POWER INTERRUPTION OF MAIN POWER SOURCE.


| 0 | LED DOWNLIGHT, VERTICAL RECESSED, ROUND 12W w/ 6" CASING FIXTURE | 83 | CIRCUIT BREAKER WITH NEMA 3R METAL ENCLOSURE | | |
|------------------------------------|---|--------------------------|---|--|--|
| - | 1-9W LED TUBE LIGHT WITH DIFFUSER, 2 FT. LENGTH (FL) | CCC 18] AC CONCENSER | ACU CONDENSER OUT DOOR UNIT WITH NEMA 3R CIRCUIT BREAKER | | |
| | 2-9W LED TUBE LIGHT WITH DIFFUSER, 2 FT. LENGTH (FL) | CIMES | ACU WALL/FLOOR MOUNTED, SPLIT TYPE, INDOOR UNIT | | |
| - | 1-18W LED TUBE LIGHT WITH DIFFUSER, 4 FT. LENGTH (FL) | | ELECTRICAL LINE | | |
| | 2-18W LED TUBE LIGHT WITH DIFFUSER, 4 FT. LENGTH (FL) | | LIGHTING SWITCH | | |
| ₩ P | EMERGENCY LIGHT (EL) | - | CIRCUIT HOMERUN | | |
| S _{1'} S _A | ONE GANG SWITCH | 1LPP1 | CIRCUIT NUMBER | | |
| S ₂ ,S _{AB} | TWO GANG SWITCH | | PANEL BOARD | | |
| S ₃ | THREE GANG SWITCH | | SERVICE ENTRANCE | | |
| S _{3W} , S _{a3W} | THREE WAY SWITCH | M | KILOWATT HOUR METER | | |
| В | TWO GANG CONVENIENCE OUTLET | CP. 1 | CONSTRUCTION POINTS | | |
| blwp. | WEATHER-PROOF TWO GANG CONVENIENCE OUTLET | | SECONDARY STEEL POLE | | |
| 0 | | | SECONDARY CONCRETE POLE | | |
| b D | TWO GANG SPECIAL POWER OUTLET TWO GANG SPECIAL POWER OUTLET (FLOOR MOUNTED) | • | PRIMARY CONCRETE POLE | | |
| • | THREE PIN ACU OUTLET | | SERVICE ENTRANCE CONCRETE PEDESTAL | | |
| YC. | ACU WINDOW TYPE | 4 | TRUSS/DOWN GUY SUPPORT | | |


VICINITY MAP





| PREPARED BY: | END USER: | REVIEWED BY: | | ENDORSED BY: | REC. APPROVAL: | \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | APPROVED BY: | PROJECT TITLE/ LOCATION: | IMPLEMENTING AGENCY: | SHT NO: |
|------------------|--------------------------------------|---------------------------------------|-----------------|--|------------------------------|---------------------------------------|---------------------------|--|----------------------------|---------|
| R. J. R. SANCHEZ | L. REYES CAMPUS ADMINISTRATOR SILANG | R. P. P. R. A. P. ROF. ELEC. ENGINEER | S. B. RAYOT JR. | B DELOS REYES DIRECTOR PLANNING AND DEVT. OFFICE | M. L. D. TEPORA VPPD CVSU | J. X. B. NEPOMUCENO VPASS CVSU | A. D. ROBLES PRES CVSU | IMPROVEMENT OF ELECTRICAL POWER SYSTEM OF CVSU SILANG CAMPUS CAVITE STATE UNIVERSITY SILANG CAMPUS | CAVITE STATE UNIVERSITY | E - 1 |












| | - And Andrews | DEINEODOEMENT | NO. OF TIES & SPACING |
|--------|-----------------|-------------------|--|
| COLUMN | DIMENSION | REINFORCEMENT | NO. OF TIES & SPACING |
| C1 | 200 MM X 200 MM | 4 - 16mm Ø R.S.B. | 2 SETS OF 10mm Ø TIES @ 2-50mm, 4-75mm, 6-100mm, REST @ 200mm O.C. |

SCHEDULE OF FOOTINGS REINFORCEMENT THICKNESS SIZE (LxW) **TYPE DEPTH** NAME BOTTOM TOP ALONG L ALONG W ALONG L ALONG W 4-16 MM Ø @ 150 MM 4 -16 MM Ø @ 150 MM 800 x 800 MM 1000 MM 200 MM F1 **ISOLATED**

— 1.02 → 4.00 - 1.02 -2.70 TRUSS 0.60





NOTE:

- USE THE FOLLOWING:

 2 1.5" X 1.5" X ½" THK. ANGULAR BAR FOR TOP CHORDS, BOTTOM CHORDS, & KING POSTS ON TRUSS 1 & LT1

 2 1.5" X 1.5" X ½" THK. ANGULAR BAR FOR WEB MEMBERS ON TRUSS 1 & LT1

 6 mm THICK GUSSET PLATES ON ALL JOINTS

 50mm x 150mm x 1.5mm CEE PURLINS SPACED @ 0.60m O.C.



SCHEDULE OF BEAMS

| BEAM | DIMENSION | SUPPORT | | MID-SPAN | | BAR ARRANGEMENT | | STIRRUPS REMARKS | ADDT. REMARKS |
|------|---------------|-----------|-----------|-----------|-----------|-----------------|----------|--|--|
| | | TOP | воттом | TOP | воттом | SUPPORT | MID-SPAN | | LIOFO |
| ТВ | 200mm X 300mm | 2-16 MM Ø | 2-16 MM Ø | 2-16 MM Ø | 2-16 MM Ø | | | 10mm Ø STIRRUPS 4 - 50mm, 6 - 75mm, 6 -100mm REST @ 200mm O.C. | USE 2 - 12mm Ø STIFFENER BARS |
| RB | 200mm X 300mm | 2-16 MM Ø | 2-16 MM Ø | 2-16 MM Ø | 2-16 MM Ø | | | - DO - | - DO - |

SHT NO: IMPLEMENTING AGENCY: PROJECT TITLE/ LOCATION: APPROVED BY: REC. APPROVAL ENDORSED BY: REVIEWED BY: END USER: IMPROVEMENT OF ELECTRICAL POWER CAVITE STATE M. D TEHORA S-1 J. X. B. NEPOMUCENO VPASS CVSU SYSTEM OF CVSU SILANG CAMPUS UNIVERSITY S. B BAYOT JA O. B. DELOS REYES
DIRECTOR PLANNING AND DEVT. OFFICE SILANG CAMPUS CAVITE STATE UNIVERSITY